



India

Delighting You Always

PIXMA GM4070



Print



Print Head / Ink

Type	Permanent (Replaceable)
Number of Nozzles	Black: 640 nozzles (Optional Colour: 1 152 nozzles)
Ink Cartridges	GI-70 (Pigment Black) Optional: CL-741, CL741XL
Printing Resolution	600 (horizontal) ^{*1} x 1 200 (vertical) dpi

Print Speed^{*2}

Based on ISO/IEC 24734

Click [here](#) for summary report

Click [here](#) for Document Print and Copy Speed
Measurement Conditions

Document (ESAT/Simplex)	13.0 images per minute (black) / 8.8 ipm (colour)
-------------------------	---

Photo (10.16 x 15.24cm) (PP-201/Borderless)	-
---	---

Printable Width	203.2 mm (20.32cm), Borderless: 216 mm (21.59cm)
-----------------	--

Printable Area

Bordered Printing	#10 Envelope/DL Envelope: Top 8mm / Bottom 12.7mm / Right 5.6mm / Left 5.6mm I / LGL: Top 3 mm / Bottom 5 mm / Right 6.3 mm / Left 6.4 mm Others: Top 3mm / Bottom 5mm / Right 3.4mm / Left 3.4mm
-------------------	--

Bordered Auto 2-Sided Printing	Top / Bottom margin: 5mm Left / Right margin: 3.4mm (I: Left: 6.4mm, Right: 6.3mm)
--------------------------------	---

Support Media

Rear Tray	Plain Paper (64 - 105 g/m ² (gsm)) High Resolution Paper (HR-101N) Envelope
-----------	--

Cassette	Plain Paper (64 - 105 g/m ² (gsm))
----------	---

Paper Size

Rear Tray	A4, A5, B5,I, LGL, Envelopes (DL, COM10), Card Size (91 x 55mm) [Custom size] width 55 - 215.9mm, length 89 - 676mm
Cassette	A4, A5, B5,I [Custom size] width 148.0 - 215.9mm, length 210 - 297mm
Paper Handling (Number)	
Rear Tray	Plain Paper (A4, 64 g/m ² (gsm)) = 100 High Resolution Paper (HR-101N) = 80
Cassette	Plain Paper (A4, 64 g/m ² (gsm)) = 250
Support Media for Auto 2-sided printing	
Type	Plain Paper
Size	A4, A5, B5, I
Paper Weight	
Rear Tray	Plain Paper: 64 - 105 g/m ² (gsm)
Cassette	Plain Paper: 64 - 105 g/m ² (gsm)
Ink End Sensor	Electrode type and dot count type combined Optional Colour Cartridge; Dot count

Print Head Alignment	Auto/Manual
Scan ^{*3}	
Scanner Type	Flatbed
Scanner Method	CIS (Contact Image Sensor)
Optical Resolution ^{*4}	1 200 x 2 400 dpi
Optical resolution scan is available, only when you use TWAIN Driver.	
Scanning Bit Depth (Input/Output)	
Grayscale	16 bit/8 bit
Colour	RGB each 16 bit/8 bit
Line Scanning Speed ^{*5}	
Grayscale	1.5 ms/line (300 dpi)
Colour	3.5 ms/line (300 dpi)
Document Size	
Flatbed	A4/I (216 x 297mm)
ADF	A4/I/LGL

Copy

▼

Document Size	A4/I
Compatible Media	
Size	A4/A5/B5/I/LGL/Card Size (91 x 55mm)
Type	Plain Paper
Image Quality	3 positions (Economy, Standard, High)
Density Adjustment	9 positions, Auto intensity (AE copy)
Copy Speed* ⁶	
Based on ISO/IEC 24734	
Click here for summary report	
Click here for Document Print and Copy Speed	
Measurement Conditions	
Document (B&W) (sFCOT/Simplex) / (sESAT/Simplex)	12s / 10.7 images per minute
Document (ADF): Black ESAT/Simplex	11.5 images per minute

Network

Protocol

SNMP, HTTP, TCP/IP (IPv4/IPv6)

Wired LAN

Network Type	IEEE802.3u (100BASE-TX) IEEE802.3 (10BASE-T)
Data Rate	10M/100Mbps (Auto switchable)
Wireless LAN	
Network Type	IEEE802.11n / IEEE802.11g / IEEE802.11b
Frequency Band	2.4 GHz
Channel ^{*7}	1 - 13
Security	WEP64/128 bit WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)
Direct Connection (Wireless LAN)	Available

Printing Solutions

▼

Canon Print Service (for Android)	Available
PIXMA Cloud Link (from smartphone/tablet)	Available
Canon PRINT	Available

System Requirements^{*8}

▼

Windows 10 / 8.1 / 7 SP1
(operation can only be guaranteed on a PC with a pre-installed Windows 7)

Mac: N/A

General Specifications

▼

Operation Panel

Display	5.08 cm LCD
---------	-------------

Language	32 Selectable Languages: Japanese / English / German / French / Italian / Spanish / Dutch / Portuguese / Norwegian / Swedish / Danish / Finnish / Russian / Czech / Hungarian / Polish / Slovene / Turkish / Greek / Simplified Chinese / Traditional Chinese / Korean / Indonesian / Slovakian / Estonian / Latvian / Lithuanian / Ukrainian / Romanian / Bulgarian / Thai / Croatian / Vietnamese
----------	---

ADF

Paper Handling (Plain Paper)	A4, l = 35, LGL = 5, others = 1
------------------------------	---------------------------------

Interface	Hi-Speed USB 2.0
-----------	------------------

PictBridge (Wireless LAN / LAN)	Available
---------------------------------	-----------

Operating Environment^{*9}

Temperature	5 - 35°C
Humidity	10 - 90% RH (no dew condensation)
Recommended Environment ^{*10}	
Temperature	15 - 30°C
Humidity	10 - 80% RH (no dew condensation)
Storage Environment	
Temperature	0 - 40°C
Humidity	5 - 95% RH (no dew condensation)
Quiet Mode	Available
Acoustic Noise (PC Print)	
Plain Paper (A4, B/W) ^{*11}	50.5dB
Power	AC 100-240 V, 50/60 Hz
Power Consumption	
OFF	0.3 W
Standby (scanning lamp is off)	0.8 W
USB connection to PC	

Standby (all ports connected, scanning lamp is off) [EU only - for ErP Lot 26 regulation]	1.7 W
Time to enter Standby mode [EU only - for ErP Lot 26 regulation]	11m 9s
Printing ^{*12} USB connection to PC	10 W
Environment	
Regulation	RoHS (EU, China), WEEE (EU)
Duty Cycle	15 000 pages/month
Dimension (WxDxH)	
Factory Configuration	403 x 369 x 234mm
Output/ADF trays extended	403 x 701 x 305mm
Weight	9.2kg

Page Yield

▼

Plain Paper (A4 pages) (ISO/IEC 24712 test file) ^{*13}	Standard: GI-70 PGBK ^{*14} : 6 000 Economy ^{*15} : GI-70 PGBK: 8 300 Optional:
--	--

1. Ink droplets can be placed with a pitch of 0.000529167cm
2. Document print speeds are the average of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734.
Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper.
Plus Glossy II and does not take into account data processing time on host computer.
Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
3. TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
4. Optical resolution is a measure of hardware sampling resolution, based on ISO 14473 standard.
5. The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not included.
6. Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183.
Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC 24735.
Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm-up time.
7. 1-11 in US, CND, LTN, BRA, TW and HK.
8. Please visit <http://asia.canon> to check OS compatibility and to download the latest driver updates.
9. The performance of the printer may be reduced under certain temperature and humidity conditions.
10. For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.
11. Acoustic Noise is measured based on ISO7779 standard with default setting.
12. Print: When printing ISO/JIS-SCID N2 on A4 size plain paper using default settings.
13. Declared yield value in accordance with ISO/IEC 24711 (for A4 size) using ISO/IEC 24712 test file, and ISO/IEC 29102 (for 10.16 x 15.24cm size) using ISO/IEC 29103 test file. Values obtained by continuous printing.
14. This printer is a monochrome printer.
Print colour document with optional colour cartridge.
Once the installed colour cartridge is depleted, please replace with a new colour cartridge or a contact protector has to be installed.
15. The economy mode reduces the black ink consumption by lowering the density, 38% more pages than the standard mode can be printed.

The page yield (A4 size) is based on the consumption data from the succeeding ink bottle but not the first ink bottle. Page yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart under ideal print conditions & continuous printing simulation with the replacement after initial setup. Mentioned print yield is from the replacement set of 4-ink bottles (C/M/Y/BK). Black bottle contains 170ml ink and each colour bottle contains 70ml of ink. Page yield varies significantly depending on contents printed and other factors.

- You need to install ink bottles of all colours whether you perform black and white printing or colour printing. If any of the ink bottles is not installed, an error occurs and you cannot perform printing.
- Even when black-only or grayscale printing is selected, depending on the printing material and driver settings used, colour inks might still be consumed when printing. When the remaining ink level of any ink tank falls below the lower limit line, Canon recommends that you refill that ink bottle with the corresponding colour of ink.
- During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles with ink. Therefore, the page yield of the initial bundled set of ink bottles will be lower than that of the subsequent sets of bottles.
- To keep printer's performance, Canon printer performs cleaning automatically according to its condition. When the printer performs cleaning, a small amount of ink is consumed.
In this case, all colours of ink may be consumed.

[Cleaning function]

The cleaning function helps the printer to suck air bubbles or ink itself from the nozzle and thus prevents print quality degradation or nozzle clogging.

- The repairing parts for printers will be available five years after production is discontinued. Depending on your model, we may ask you to replace it with a new one, or one with almost the same performance as a maintenance service. In this case, it may be that you cannot use supplies or accessories for your model or the compatible OS will be changed.
- The warranty term for details, contact a Canon-authorized sales representative in the country or region you live in. The warranty covers only the printer main body excluding consumables such as print media and ink / ink bottles even during the warranty period.
- To obtain good printing quality, use up ink within six months after opening.
- Please take note that if the printer fault or breakdown is due to the usage of non-genuine inks, repair charges are applicable even if the claim is within the warranty period.
- Using non-genuine inks may affect the printer's performance and / or the print quality. In some rare occasions, although there are no safety issues, using non-genuine inks has caused overheating of the print head and smoke emission from the print head due to the absence of an ingredient found in genuine ink. (Does not apply to usage of all non-genuine inks).
- Depending on your terminal, such as a computer or a smartphone, or the operating system of your terminal, such as your computer or smartphone, the estimated ink level information or message displayed on the screen of your terminal may be different from the information or message displayed on the operation panel of the printer. Also, a part of the estimated ink level message displayed on the operation panel of the printer may not be displayed and / or may be displayed at a different point in time. Canon recommends that you use the information and message displayed on the operation panel of the printer as your reference. Note, however, that such information and message are displayed items serve only as a guideline information.
- Information on Received Faxes

By default, received faxes will be printed immediately after they are received. In addition, faxes will be stored in the printer's memory automatically when they are received.

However, the printer's memory has an upper limit on the number of faxes or subjects it can contain. When the amount of stored fax reaches the upper limit of the printer's memory, faxes stored latest will overwrite those stored earliest.

As long as paper is loaded, the printer will perform printing even when the ink remaining is insufficient. Therefore, in case ink remaining is low, printed faxes may be unclear due to blurring of ink. In such case if the amount of stored faxes has reached its upper limit of the printer's memory, faxes stored in the printer's memory will be deleted in order from the earliest. As a result, you may not be able to see faxes either using printed material or the printer's memory.

Therefore, if you use the fax capabilities, make sure sufficient ink remains in the ink tank in advance. In addition, we recommend you refill the ink tank early so that ink does not become insufficient while fax printing is in progress. Visually inspect the remaining ink in the printer's ink tank.

Moreover, we recommend you check printed pages immediately after faxes are received. If a fax remains in the printer's memory, you can reprint it after refilling the ink tank.

If [Do not print] is selected for [Received documents] on [Auto print settings] under [FAX settings] on the operation panel of the printer, received faxes will not be printed immediately. Instead, faxes are stored in the printer's memory automatically and you can select and print those stored from the printer's memory. In this setting, the printer does not receive faxes if the printer's memory reaches its upper limit. Thus, stored faxes are not overwritten automatically.

-
- Prices, specifications, availability and terms of offers may change without notice.
 - Products / Services may be manufactured by and/or supplied to us by third party manufacturers / suppliers for distribution / resale (non-Canon brand products).
 - Prices above are maximum retail price (MRP) and may change without prior notice.
-
-